

# **Safety Data Sheet** Spartan Chemical Company, Inc.

Revision Date: 11-Aug-2015

# 1. PRODUCT AND COMPANY IDENTIFICATION

**Product Identifier** 

**Product Name:** STAINLESS STEEL CLEANER POLISH

**Product Number:** 6310

Cleaning agent **Recommended Use:** 

**Uses Advised Against:** For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

> 1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

### 2. HAZARDS IDENTIFICATION

**GHS Classification** 

Flammable Aerosols Category 1 Gases Under Pressure Liquefied gas

**GHS Label Elements** 

**Signal Word:** 

Danger Symbols:



**Hazard Statements:** 

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated

**Precautionary Statements:** 

Keep away from heat/sparks/open flames/hot surfaces. — No smoking Prevention:

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

Response:

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Protect from sunlight. Do not expose to temperatures exceeding 122°F (50°C) Store in a Storage:

well-ventilated place

Not Applicable Disposal:

Hazards Not Otherwise Classified: Not Applicable

Other Information: · May cause skin irritation.

- · May cause eye irritation.
- · May be harmful if swallowed.
- Inhalation of vapors or mist may cause respiratory irritation.

Revision Date: 11-Aug-2015

· Keep out of reach of children.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	40-70
petroleum distillates	64741-44-2	10-30
N-butane	106-97-8	3-7
petroleum distillates	64742-88-7	1-5
propane	74-98-6	1-5
polydimethylsiloxane	63148-62-9	1-5
decaglyceryl monooleate	9007-48-1	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

## 4. FIRST AID MEASURES

-Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Wash with soap and water. If skin irritation occurs: Get medical attention. -Skin Contact:

-Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a

poison control center or physician if you feel unwell.

Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious -Ingestion:

person. Get medical attention if you feel unwell.

Note to Physicians: Treat symptomatically.

### 5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: Water spray (fog), Foam

Extremely flammable aerosol. Exposure to high temperature may cause containers to burst. Specific Hazards Arising from the

Chemical: Bursting aerosol containers may be propelled from fire at high speed.

**Hazardous Combustion Products:** May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

**Protective Equipment and** Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full **Precautions for Firefighters:** 

protective gear. Water may be used to cool closed containers to prevent pressure build-up

and possible auto ignition or explosion when exposed to extreme heat.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions: Environmental Precautions:** Methods for Clean-Up:

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required.

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

## 7. HANDLING AND STORAGE

Advice on Safe Handling:

Handle in accordance with good industrial hygiene and safety practice. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Wash thoroughly after handling.

Revision Date: 11-Aug-2015

**Storage Conditions:** NFPA 30B Level 1 Aerosol. Do not store in direct sunlight or above 122 F° / 50 C°.

Exposure to high temperature may cause containers to burst. Keep out of the reach of

children.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** 

	Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
	N-butane	TWA: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
	106-97-8		(vacated) TWA: 1900 mg/m <sup>3</sup>	TWA: 1900 mg/m <sup>3</sup>
ı	propane	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
	74-98-6	1	TWA: 1800 mg/m <sup>3</sup>	TWA: 1000 ppm
			(vacated) TWA: 1000 ppm	TWA: 1800 mg/m <sup>3</sup>
			(vacated) TWA: 1800 mg/m <sup>3</sup>	

Provide good general ventilation. **Engineering Controls:** 

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

engineering controls should be considered.

Personal Protective Equipment

**Eye/Face Protection: Skin and Body Protection: Respiratory Protection:** 

Not required with expected use. Not required with expected use. Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

**General Hygiene Considerations:** Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Aerosol	
Color:	White	
Odor:	Lemon	
pH:	8.0-9.0	
Melting Point / Freezing Point:	No information available.	
Boiling Point / Boiling Range:	100 °C / 212 °F (Product without propellant)	
Flash Point:	< -18 °C / < 0 °F (Propellant-estimated)	
Evaporation Rate:	<1 (Butyl acetate = 1)	
Flammability (solid, gas)	No information available.	
Upper Flammability Limit:	No information available.	
Lower Flammability Limit:	No information available.	
Vapor Pressure:	No information available.	
Vapor Density:	No information available.	
Specific Gravity:	0.94 (Product without propellant)	
Solubility(ies):	No information available.	
Partition Coefficient:	No information available.	
Autoignition Temperature:	No information available.	
Decomposition Temperature:	No information available.	
Viscosity:	No information available.	

# 10. STABILITY AND REACTIVITY

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Stable under normal conditions. **Chemical Stability:** 

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Extremes of temperature and direct sunlight. **Conditions to Avoid: Incompatible Materials:** Strong oxidizing agents. Strong acids.

Revision Date: 11-Aug-2015

**Hazardous Decomposition** 

Products:

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

# 11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eye Contact: Pain and redness. -Skin Contact: Drying of the skin.

-Inhalation: Nasal discomfort and coughing. -Ingestion: Pain, nausea, vomiting and diarrhea.

Immediate, Delayed, Chronic Effects

**Product Information:** Data not available or insufficient for classification.

Target Organ Effects: Central nervous system.

**Numerical Measures of Toxicity** 

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 24279 mg/kg ATEmix (dermal): 9524 mg/kg ATEmix (inhalation-gas): 3021468 mg/l

**Component Acute Toxicity Information** 

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50	
water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available	
petroleum distillates 64741-44-2	= 5000 mg/kg (Rat)	> 2000 mg/kg ( Rabbit )	= 1700 mg/m <sup>3</sup> ( Rat ) 4 h	
N-butane 106-97-8	Not Available	Not Available	= 658 mg/L (Rat) 4 h	
petroleum distillates 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg ( Rabbit )	> 5.28 mg/L (Rat) 4 h	
propane 74-98-6	Not Available	Not Available	= 658 mg/L (Rat) 4 h	
polydimethylsiloxane 63148-62-9	> 17 g/kg (Rat)	> 2 g/kg (Rabbit)	Not Available	

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

# 12. ECOLOGICAL INFORMATION

**Ecotoxicity** 

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
petroleum distillates 64742-88-7	450: 96 h Pseudokirchneriella subcapitata mg/L EC50	800: 96 h Pimephales promelas mg/L LC50 static	Not Available	100: 48 h Daphnia magna mg/L EC50

Persistence and Degradability: No information available. No information available. Bioaccumulation: Other Adverse Effects: No information available.

# 13. DISPOSAL CONSIDERATIONS

**Disposal of Wastes:** Dispose of in accordance with federal, state and local regulations.

**Contaminated Packaging:** Pressurized container: Do not pierce or burn, even after use. Dispose of in accordance with

federal, state and local regulations.

# 14. TRANSPORT INFORMATION

•

Revision Date: 11-Aug-2015

DOT:
UN/ID No:
UN1950
Proper Shipping Name:
Aerosols

Hazard Class: 2.1

**Special Provisions:** This product meets the exception requirements of section 49 CFR 173.306 as a limited

quantity and may be shipped as a limited quantity.

IMDG:

UN/ID No: UN1950 Proper Shipping Name: Aerosols

Hazard Class: 2.1

Additional information: Limited Quantity

## 15. REGULATORY INFORMATION

#### TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

#### **SARA 313**

This product does not contain listed substances above the "de minimus" level

#### SARA 311/312 Hazard Categories

Acute Health Hazard:

Chronic Health Hazard:

No
Fire Hazard:

Sudden release of pressure hazard:

Reactive Hazard:

No
No

#### **California Proposition 65**

This product is not subject to warning requirements under California Proposition 65.

## **16. OTHER INFORMATION**

NFPA Health Hazards: 1 Flammability: 2 Instability: 0 Special: N/A

HMIS Health Hazards: 1 Flammability: 2 Physical Hazards: 2

**Revision Date:** 11-Aug-2015 **Reasons for Revision:** Section 14 and 15

#### Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**